

# FOODMAX AW 46

Productcode: 264000401

## Range of multipurpose lubricating oils for the food industry

This product is formulated using specially selected highly refined base stocks in combination with the latest additive technology. The product is nontoxic and suitable for use in applications where incidental contact with food or raw materials during the production is possible or likely. Thanks to its great performance characteristics and carefully chosen additives, the oils can be used in most applications in the manufacturing process in the food production and processing industry. The product available in a wide range and is NSF approved.

## Typical Performance Data

Property	Test method	Value
Density @ 20 °C, kg/dm <sup>3</sup>	ASTM D1298	0.850
Viscosity @ 40 °C, mm <sup>2</sup> /s	ASTM D445	46
Viscosity index	ASTM D2270	105
Pour point, °C	ASTM D97	-18
Flash point, °C	ASTM D92	210
TAN, mg KOH/g	ASTM D664	0.8
Aniline point, °C	ASTM D661	105
Copper corrosion 3h @ 100 °C	ASTM D130	1a
Rust test A (distilled water)	ASTM D665	Pass
Water Separability, ml oil/ml water/ml emulsion	ASTM D1401	40/40/0 (20')
NSF registration		138238
Kosher approved		Yes
Halal approved		Yes

All performance data on this Technical Data Sheet are indicative only and can vary during production.